


Product Benefits & Features

No sorting needed. Mixed loads each time evenly dried with MixCare

MixCare provides powerful yet gentle drying for mixed loads of cottons and synthetics, ensuring clothes are evenly dried with no sorting needed.


SensiCare – optimal drying to preserve your clothes

SensiCare measures the temperature and humidity of each load, adjusting the time and energy consumption accordingly, so garments are protected from overheating and overdrying. Clothes look and feel new for longer without wasting energy.


Even drying results for XL capacity loads with family sized Bedlinen XL

The family Bedlinen XL programme provides even drying results for XL loads, including bedlinen sets, without needing to re-start your dryer.


EasyClean Filter – for an energy-efficient machine

The EasyClean Filter is easy to clean and keeps your machine running at its best, helping to keep energy efficiency.


Anticrease helps reducing wrinkles

Anticrease allows the drum to rotate in both directions periodically, helping reduce wrinkles in clothes during the cooling down phase.

- Heat pump technology achieves unprecedented energy efficiency
- Delay start option
- Sensor dryer: the dryer senses when the clothes are dried to the level specified
- Additional time controlled drying programs
- Optional accessories: Direct drain hose, Stacking kit
- Accessories included: Condenser Slots Brush

Product Specification

Nordic_TD_FamilyName	600 GentleCare	Nordic_TD_SensiDry_or_GentleCare	-
Drying capacity, kg (3rd Gen)	8.0	Nordic_TD_ProSense_or_SensiCare	SensiCare
Energy efficiency class, legal (E20)	D	Net weight, kg	48.2
Condensation efficiency class, (3rd gen)	C	Product Number Code	916 900 701
Condensation Efficiency, % (3rd Gen)	82	Bar code	7333394154701
Weighted average energy consumption / 100 cycles, kWh (E20)	119		
Door hinges	Right Reversible By User		
Drum volume, l	118		
Tank capacity, l	5.32		
Airborne acoustical noise emissions, dBA re 1 pW	64		
Airborne acoustical noise emission class	B		
Dimensions HxWxD in mm	850x596x638		
Depth max, mm	662		
Depth open door	1107		
Cord length, m	1.45		
Connected load, W	750		
Volt, V	230		
Nordic_TD_Refrigerant_Volume	R290/0.12		
Frequency, Hz	50		