



Precise storage. For all varieties

The 5000 Cellaring Core Single-Zone can be set between 5–18°C for serving, or 12–14°C for cellaring all varieties for short or long-term.

Product Benefits & Features

Trust the temperature. With Single-Zone Pro

The Single-Zone Pro wine cabinet can be set at any temperature between 5–20°C for serving or kept between 12–14°C, the perfect temperature for cellaring all your wines.



Preserve wine with Cellaring 3 Fundamentals

We help you treat your wine properly by providing storage that offers Cellaring 3 Fundamentals: temperature stability, a vibration free environment and a dark storage area.

- Touch control
- Telescopic guides for easy entry and overview of your bottles
- Audible & visual high temperature warning signal
- Door hinges placement: Right & Reversible

Product Specification

Energy efficiency class (EEC) (E20)	G	Control position	Cabinet Top, Internal
Number of zones	1	Total Volume (l)	58
Number Of Bottles WINE STORAGE Compartment	20	Max. ambient temp, °C	38
Min. ambient temp, °C	16	Height, mm	820
Lamps fridge	Internal. LED	Width, mm	295
Total Unfrozen Volume (l)	58	Depth, mm	571
Noise Class	C	Built in height, mm	822
Annual energy consumption (EL), [kWh/y]	138	Built in width, mm	300
Climate class E20	N-ST		
Noise, dB(A) E20	40		
Installation type	Built_In		
Storage Volume WINE STORAGE Compartment	58		
Main colour	Black Glossy Glass		
Connected load, W	60		
Cord length, m	1.8		
Net weight, kg	28.6		
Gross weight, kg	33		
Installation Type	Bi Wide Door		
Door hinges	Right & Reversible		
Plug Type	Euro Moulded		
Frequency, Hz	50		
Product Partner Code	All Open		

