



X11L Series Spec

Model	75X11L	85X11L	98X11L
Basic Information			
Size	75	85	98
Resolution	3840*2160 (16:9)	3840*2160 (16:9)	3840*2160 (16:9)
Product Type	SOQ-Mini LED	SOQ-Mini LED	SOQ-Mini LED
Chassis Platform	M7655	M7655	M7655
DDR	8GB	8GB	8GB
EMMC	64GB	64GB	64GB
Local Dimming	Yes	Yes	Yes
GPU	A734	A734	A734
OS	GTV	GTV	GTV
Wireless	WiFi 6	WiFi 6	WiFi 6
Bluetooth	BT 5.4	BT 5.4	BT 5.4
Power Supply	AC 220V-240V 50Hz	AC 220V-240V 50Hz	AC 220V-240V 50Hz
Power Consumption (TV On)	480W	740W	870W
Power Consumption (Standby)	< 0.3W	< 0.3W	< 0.3W
ECO Energy Efficiency	Yes	Yes	Yes
Panel Specification			
Brightness (cd/m2)	High HDR Brightness	High HDR Brightness	High HDR Brightness
Viewing Angle (H/V) (Open Cell)	178°/178° (typ.)	178°/178° (typ.)	178°/178° (typ.)
Color	1.07G 8bit+FRG, Quantum Dots	1.07G 8bit+FRG, Quantum Dots	1.07G 8bit+FRG, Quantum Dots
Refresh Rate (Hz)	144Hz (VRR 48-288Hz/DLG 288Hz)	144Hz (VRR 48-288Hz/DLG 288Hz)	144Hz (VRR 48-288Hz/DLG 288Hz)
MEMC	120Hz	120Hz	120Hz
Color Gamut	BT2020 100%(Area ratio)	BT2020 100%(Area ratio)	BT2020 100%(Area ratio)
Picture			
Picture Mode	Intelligent / Vivid / Low Power / Sports / Movie / Game / PC / FilmMaker	Intelligent / Vivid / Low Power / Sports / Movie / Game / PC / FilmMaker	Intelligent / Vivid / Low Power / Sports / Movie / Game / PC / FilmMaker
Picture certification	HDR / HDR10+ / HLG / Dolby Vision IQ / IMAX Enhanced / FreeSync Premium Pro	HDR / HDR10+ / HLG / Dolby Vision IQ / IMAX Enhanced / FreeSync Premium Pro	HDR / HDR10+ / HLG / Dolby Vision IQ / IMAX Enhanced / FreeSync Premium Pro
Audio			
Special Feature	B&O	B&O	B&O
Channel Configuration	/	/	/
Audio Power Output (THD=7%)	/	/	/
Sound Mode	Movie / Music / Speech / Game / Sports / Night / Custom	Movie / Music / Speech / Game / Sports / Night / Custom	Movie / Music / Speech / Game / Sports / Night / Custom
Audio Certification	Dolby Atmos / B&O / Flex T	Dolby Atmos / B&O / Flex T	Dolby Atmos / B&O / Flex T
Feature			
Google Assistant	Voice input via remote control.	Voice input via remote control.	Voice input via remote control.
Input Method	Hands-free voice input via built-in MIC	Hands-free voice input via built-in MIC	Hands-free voice input via built-in MIC
HDMI CEC	Yes	Yes	Yes
Connection authentication	Yes	Yes	Yes
DTV Programme only	PVR/Timeshift, EPG, Subtitle, Parental Control	PVR/Timeshift, EPG, Subtitle, Parental Control	PVR/Timeshift, EPG, Subtitle, Parental Control
Multimedia Spec (USB)			
Music	MP3, MKV, WMA, AVI	MP3, MKV, WMA, AVI	MP3, MKV, WMA, AVI
Picture	JPEG/PNG/BMP/HEIF	JPEG/PNG/BMP/HEIF	JPEG/PNG/BMP/HEIF
Multimedia Video Decoder	H.264, H.265, MPC1/2/4, WMV, VC1, VP8, VP9, AV1	H.264, H.265, MPC1/2/4, WMV, VC1, VP8, VP9, AV1	H.264, H.265, MPC1/2/4, WMV, VC1, VP8, VP9, AV1
Video Format up to	Up to 4K@60Hz	Up to 4K@60Hz	Up to 4K@60Hz
USB Mouse/Key Board	Yes	Yes	Yes
Accessory			
Operation Manual	English (default)	English (default)	English (default)
Remote Control and Batteries	RC933B (with 2AAA batteries)	RC933B (with 2AAA batteries)	RC933B (with 2AAA batteries)
Base Stand Integrated in Package	Yes	Yes	Yes
AC Power Cord	1 pcs	1 pcs	1 pcs
Dimension&Weight			
Set Size with Stand (WxHxD)	1658*380*1024	1880*380*1150	2168*420*1313
Set Size without Stand (WxHxD)	1658*24*979	1880*21*1104	2168*21*1267
Stand (Base) (WxD)	1496*380	1718*380	2005*420
Adjust Stand	No	No	No
Adjustable Width	/	/	/
Adjustable Height	/	/	/
Support Floor Stand	No	Yes	Yes
Set Weight with Stand	40.5	52.6	67.5
Set Weight without Stand	39	51.2	66
Gross Weight with Packaging (Kg)	51.6	76.3(with out pallet)	102(without pallet)/115.5 (with pallet)
Carton Dimensions LxWxH (mm)	1850*164*1125	2060*291*1288(with out pallet)	2398*520*1489(with out pallet)
Container Loading—20 feet (pcs)	88	20(with pallet)	2395*330*1594(with pallet)
Container Loading—40 feet (pcs)	178	44(with pallet)	14(with pallet)
Container Loading—40 feet High (pcs)	178	44(with pallet)	35(with pallet)
VESA Mounting	WM34-85/WM54A-85(ultrathin)	WM34A-115/WM54A-115(ultrathin)	WM34A-115/WM54A-115(ultrathin)
VESA Spec (mm)	600*400 (WM34-85) 1200 (WM54A-85)	600*400(WM34A-115) 1500(WM54A-115)	600*400(WM34A-115) 1661(WM54A-115)

75/85/98X11L

