



Effectively and easily cleans your dishes

The Electrolux 500 series gives you clean dishes dried with fresh air. Enjoy easy operation – just choose cycle length. Generous loading space and height-adjustable upper basket.

Product Benefits & Features



Uses fresh air to finish drying

AirDry uses fresh air to finish drying the dishes. This makes the drying performance up to 3x better compared to a closed-door system. The door automatically opens towards the end of the cycle to let in fresh air.



Easy, time-based program selection

With TimeSet you don't have to figure out what program to use. Just decide how soon you want your dishes to be ready, set the cycle length and press start.




A light shines onto the floor to show the dishwasher is running

LightOnFloor® shines a white light onto the floor whilst a cycle is under way. The light turns off when the cycle is complete and the dishes are ready to be unloaded.



Clean dishes in only 30 minutes

When you need clean dishes in a hurry, use the QuickClean to get clean dishes in 30 minutes.



MachineClean cycle maintains dishwasher performance

Keep your dishwasher running at its best with the MachineClean cycle. The specifically designed programme and detergent work together to remove limescale and greasy build-up, so you can always enjoy spotless dishwashing results.

- LightOnFloor
- Touch control for programs and functions selection
- Delay Start
- Indications for salt and rinse aid
- AirDry
- Door Fit Kit included
- Auto Off function
- Upper basket with 2 rows of fixed tines, Foldable cup shelves, plastic handle ELUX
- Lower basket with Low round rack frame, 2 rear foldable tines
- Options: PowerBoost
- Dishwasher programmes: 90 Minutes, AUTOClean, ECO, MachineClean, QuickClean, QuickRinse

Product Specification			
Installation	FI	Water consumption / cycle IE20	9.9
Rated capacity psE20	13	Hinges	Sliding up to 10kg
Energy efficiency class, legal (E20)	C	Connected load, W	1950
Airborne acoustical noise emissions, dBA re 1 pW	44	Cord length, m	1.5
Door colour	None	Outlet hose length, cm	150
Dimensions_Dishwasher_FSBU_DK	820-900x600x550	Required fuse (A)	10
Number of programs	6	Inlet hose length, cm	150
Number of temperatures	3	Inlet hose type	Aqua control
Dimensions HxWxD in mm	818x596x550	Anti-flood device	Floating switch
Airborne acoustical noise emission class	B	Water supply	Cold or Hot
Depth open door	1200	Upper basket, Level 1, max	190
Nordic_DW_CutleryType	Cutlery basket	Upper basket, Level 2, max	140
Nordic_DW_QuickSelect	Level 1	Lower basket, Level 1, max	270
Nordic_DW_GlassCare2G	No	Lower basket, Level 2, max	315
Beam on floor	LightOnFloor	Upper spray arm	Standard spray arm
Interior light	No	Lower spray arm	Standard
Nordic_DW_DoorFitKit	Yes	Options	PowerBoost
Cleaning performance index3 digitE20	1.121	Options available only through the App	None
Drying performance index 3 digitE20	1.061	Feet/Wheels	2 adj feet + 1 front adj rear foot (adj 0 to 8cm)
Weighted average energy consumption / 100 cycles, kWh (E20)	74	Installation in height	None
		Nordic_DW_DoorPanelHeight	645-776
		Nordic_DW_DoorPanelWeight	2-10
		Indicator program	LED