



#### Tailored drying for the most delicate items

The 700 DelicateCare Heat Pump Dryer adjusts the temperature and motion of the drum to specific fabrics, ensuring tailored care. Silks retain their shape, woolens get safely dried with no shrinkage and water repellency of outdoor garments is restored. Woolmark certified.

### Product Benefits & Features



#### DelicateCare - dries wool with no shrinkage guaranteed\*

DelicateCare uses heat pump technology to dry delicate garments with tailored drum temperatures and movements, helping clothes last longer. Even fabrics such as silk and wool are dried with superior Care. Woolmark certified.



#### No sorting needed. Mixed loads each time evenly dried with MixCare


MixCare provides powerful yet gentle drying for mixed loads of cottons and synthetics, ensuring clothes are evenly dried with no sorting needed.

\*Comparable with flat drying.



#### SensiCare – optimal drying to preserve your clothes

SensiCare measures the temperature and humidity of each load, adjusting the time and energy consumption accordingly, so garments are protected from overheating and overdrying. Clothes look and feel new for longer.



#### The Hygiene cycle removes more than 99.9% of bacteria and viruses

The Hygiene cycle runs above 60°C, drying while sanitizing items, removing 99.9% of bacteria and viruses.

- Heat pump technology achieves unprecedented energy efficiency
- DelicateCare
- Internal light for optimal visibility in the tumble dryer
- Inverter motor technology
- Delay start option
- Sensor dryer: the dryer senses when the clothes are dried to the level specified
- Additional time controlled drying programs
- Optional accessories: Direct drain hose, Stacking kit
- Accessories included: Condenser Slots Brush

**Product Specification**

Nordic_TD_FamilyName	700 DelicateCare	Required fuse (A)	5
Drying capacity, kg (3rd Gen)	8.0	Product Number Code	916 900 903
Woolmark	Woolmark Green	Bar code	7333394174983
Energy efficiency class, legal (E20)	B		
Weighted average energy consumption / 100 cycles, kWh (E20)	85		
Condensation efficiency class, (3rd gen)	B		
Airborne acoustical noise emission class	B		
Airborne acoustical noise emissions, dBA re 1 pW	63		
Connectivity	Yes		
Door hinges	Right Reversible By User		
Drum volume, l	118		
Tank capacity, l	5.56		
Dimensions HxWxD in mm	850x596x636		
Depth open door	1102		
Nordic_TD_Refrigerant_Volume	/0.149		
Cord length, m	1.45		
Connected load, W	550		
Volt, V	230		
Frequency, Hz	50		
Plug Type	Euro Moulded		

